



SIZE	ART. NO.	EAN NO.
6	990-6	7392626005174
7	990-7	7392626005181
9	990-9	7392626005204
10	990-10	7392626005211
8	990-8	7392626005341
11	990-11	7392626009400

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 990

Cut resistant glove, PU, palm-dipped, smooth finish, cut resistance level B, 13 gg, Dyneema®, Lycra®, Cat. II, white, for precision work

PROPERTIES

Extremely good fingertip sensitivity, durable, good grip, perfect fit, extra comfortable, breathable, light

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 8,4

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

DIPPING Palm-dipped

DIPPING MATERIAL PU

LINING MATERIAL 13 gg, Dyneema®, Lycra®

DEXTERITY 5

GRIP PATTERN Smooth finish

CUFF STYLE Knitwrist cuff

LENGTH RANGE 210 - 250mm

COLOUR White

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Bag OUTER MATERIAL SPECIFICATION Polyurethane

INNER MATERIAL SPECIFICATION UHMWPE, elastane

TEGERA® 990

FEATURES

Cut resistant according to 388:2016 level B, water and oil repellent palm, soft, elastic, fibreglass-free

PREVENTS RISK OF

Cut injuries, abrasion injuries, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Cut risk environments

PRIMARY AREAS OF USE

Assembly, carpentry, construction, engineering, glass industry work, inspection work, installation work, machine operating, metalwork, repair work, warehouse work, wood industry work

PRIMARY INDUSTRIES OF USE

Automotive

TYPE OF WORK

Light weight

2(3)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4X41B



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 990

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)		(4)
B) Resistance to cutting (Index)		(5)
C) Tear resistance (Newton)		(4)
D) Puncturing resistance (Newton)		(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4X41B



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com