



**Thinsulate**  
INSULATION

| SIZE | ART. NO. | EAN NO.       |
|------|----------|---------------|
| 6    | 8355-6   | 7340118317892 |
| 7    | 8355-7   | 7340118317915 |
| 8    | 8355-8   | 7340118317939 |
| 9    | 8355-9   | 7340118317953 |
| 10   | 8355-10  | 7340118317830 |
| 11   | 8355-11  | 7340118317854 |
| 12   | 8355-12  | 7340118317878 |

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 8355

Cut resistant glove, winter-lined, 0,65-0,8 mm full grain goatskin of top quality, cut resistance level B, KEVLAR® fiber, Thinsulate™ 40g, Cat. II, black, water repellent, elasticated 180°, for allround work

### PROPERTIES

Highest level of protection, extremely good fingertip sensitivity, extra flexible, very durable, perfect fit, warm

### SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 10,7

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,65-0,8 mm

LINING Winter-lined

LINING MATERIAL KEVLAR® fiber, Thinsulate™ 40g

DEXTERITY 5

FASTENING Elasticated 180°

LENGTH RANGE 230-265 mm

COLOUR Black

PAIRS PER PACKAGE/CARTON 3/60

PIECES PER BOX 0

DISPLAY Thread OUTER MATERIAL SPECIFICATION Leather, natural latex

MIDDLE MATERIAL SPECIFICATION Para-aramid

INNER MATERIAL SPECIFICATION Polyester

**CE** Cat. IIEN 420:2003  
+ A1:2009EN 388:2016  
2X31BEN 511:2006  
12X

EN ISO 11640:2012



## TEGERA® 8355

### FEATURES

Cut resistant according to 388:2016 level B, water repellent

### PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with damp, contact with cold

### PRIMARY ENVIRONMENTS OF USE

Moist environments, harsh environments

### PRIMARY AREAS OF USE

Security- and police work

### PRIMARY INDUSTRIES OF USE

Service

### TYPE OF WORK

Medium weight

2(3)

**ejendals**  
PROTECTING HANDS AND FEET**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-10

## TEGERA® 8355

### EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

| Property                                       | Level Achieved | (Maximum Performance) |
|------------------------------------------------|----------------|-----------------------|
| a) Resistance to abrasion (No. of revolutions) | 2              | (4)                   |
| b) Cut resistance (Index)                      | X              | (5)                   |
| c) Tear resistance (N)                         | 3              | (4)                   |
| d) Puncturing resistance (N)                   | 1              | (4)                   |
| e) Cut resistance, EN ISO 13997 (N)            | B              | (F)                   |
| f) Impact protection, EN 13594:2015            |                | (P)                   |

### EN 388 – Testing

(specifies the requirements that apply for each safety level).

| Level of protection/Performance level          | 1   | 2   | 3     | 4     | 5    |
|------------------------------------------------|-----|-----|-------|-------|------|
| a) Resistance to abrasion (No. of revolutions) | 100 | 500 | 2 000 | 8 000 |      |
| b) Cut resistance (Index)                      | 1,2 | 2,5 | 5,0   | 10,0  | 20,0 |
| c) Tear resistance (N)                         | 10  | 25  | 50    | 75    |      |
| d) Puncturing resistance (N)                   | 20  | 60  | 100   | 150   |      |

| Level of protection/Performance level | A | B | C  | D  | E  | F  |
|---------------------------------------|---|---|----|----|----|----|
| e) Cut resistance, EN ISO 13997 (N)   | 2 | 5 | 10 | 15 | 22 | 30 |

| Level of protection/Performance level | P                     |
|---------------------------------------|-----------------------|
| f) Impact protection, EN 13594:2015   | Pass (Level 1 ≤ 9 kN) |

EN 511:2006 Protective gloves against cold



CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
2X31B



EN 511:2006  
12X

EN ISO 11640:2012



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-10

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com