



539AA2MPI













Flame retardant, anti-static hi-vis polo shirt

The Garat is a flame retardant, anti-static hi-vis polo shirt with good moisture management properties. The long-sleeved shirt with turnover collar has undergone antibacterial treatment and protects you against exposure to UV sunlight. This comfortable and soft polo shirt increases your visibility during work thanks to the welded, segmented reflective tape on the arms, chest, stomach and back.











Flame retardant, anti-static hi-vis polo shirt

Garat - 539AA2MPI

European Standards:

- » EN ISO 11612: 2015 / A1 B1 C1 F1 » EN ISO 14116: 2015 / IND.3
- » EN 1149-5 : 2008
- » EN ISO 20471: 2013 +A1 2016 / Class 3 » EN 13758-2: 2003 + A1: 2006 / UPF 50+
- EN ISO 13688: 2013

Exterior:

- » Lay-flat collar
- » Closure with hidden press studs under flap
- » Long sleeves
- » Welded, segmented reflective tape
- » Back length 72 cm (L)

Fabric:

Jersey: 60% Protex® + 39% Viloft® + 1% AST; ± 180 g/m2

Sizes:

S - XXXL

Colour:

» FY1 Hi-Vis Yellow

Packaging:

10 pieces per box

Wash and care instructions:











SIOEN head office

Fabriekstraat 23 B-8850 Ardooie Belgium T: +32 (51) 740 800 F: +32 (51) 740 962 www.sioen-ppc.com



Discover our products © 2020 Sioen Apparel - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the Sioen Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice.

All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.