



SIZE	ART. NO.	EAN NO.
10	983-10	7392626073425
11	983-11	7392626073449
7	983-7	7392626073463
8	983-8	7392626073487
9	983-9	7392626073500

TEGERA® 983

Cut resistant glove, PU, palm-dipped, smooth finish, cut resistance level B, 15 gg, Dyneema® Diamond Technology, Lycra®, Cat. II, white, yellow, breathable back, for precision work

PROPERTIES

Extremely good fingertip sensitivity, extra flexible, durable, good grip, perfect fit, extra comfortable, very breathable, extremely light

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 10,9

SIZE RANGE (EU) 7, 8, 9, 10, 11

DIPPING Palm-dipped

DIPPING MATERIAL PU

LINING MATERIAL 15 gg, Dyneema® Diamond Technology, Lycra®

DEXTERITY 5

GRIP PATTERN Smooth finish

CUFF STYLE Knitwrist cuff

LENGTH RANGE 220 - 270mm

COLOUR White, Yellow

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Bag with euro slot OUTER MATERIAL SPECIFICATION Polyurethane

INNER MATERIAL SPECIFICATION UHMWPE, elastane

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 983

FEATURES

Cut resistant according to 388:2016 level B, high visibility colour

PREVENTS RISK OF

Cut injuries, abrasion injuries, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dirty environments

PRIMARY AREAS OF USE

Assembly, building and construction, carpentry, construction, electrical installation, glass industry work, HVAC installation, inspection work, installation work, metalwork, sheet-metal work, soil preparation, transport work, warehouse work, wood industry work

PRIMARY INDUSTRIES OF USE

Metal fabrication, machinery and equipment, MRO, automotive, building and construction

TYPE OF WORK

Light weight



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3X43B



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 983

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	3	(4)
e) Cut resistance, EN ISO 13997 (N)	B	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3X43B



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com