



TEGERA® 887

Synthetic glove, nitrile foam, palm-dipped, reinforced grip pattern, 13 gg, Lycra®, nylon, Cat. II, black, blue, water and oil repellent palm, for precision work

PROPERTIES

Good fingertip sensitivity, durable, good grip, comfortable, breathable, light

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile foam

LINING MATERIAL 13 gg, Lycra®, Nylon

DEXTERITY 5

GRIP PATTERN Reinforced grip pattern

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

LENGTH RANGE 220 - 260mm

COLOUR Black, Blue

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Bag with euro slot OUTER MATERIAL

SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION Nylon, elastane

SIZE	ART. NO.	EAN NO.
7	887-7	7392626040250
8	887-8	7392626040267
9	887-9	7392626040274
10	887-10	7392626040281
11	887-11	7392626040298

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4132X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

TEGERA® 887

FEATURES

Breathable back, water and oil repellent palm

PREVENTS RISK OF

Abrasion injuries, grazes, scratches, lacerations, contact with dirt, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Slippery environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Airport work, assembly, building and construction, carpentry, construction, electrical installation, fine assembly, HVAC installation, inspection work, installation work, machine operating, painting, soil preparation, warehouse work

PRIMARY INDUSTRIES OF USE

Machinery and equipment, MRO, automotive, transportation, utilities

TYPE OF WORK

Light weight

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 887

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	3	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4132X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com