



TEGERA® 10PG

Chemical protection glove, 0,7* mm (*chem-layer) PVC (Vinyl), smooth finish, cotton, interlock, Cat. III, red, oil and grease resistant, for heavy work

PROPERTIES

Very durable

SPECIFICATION

TYPE OF GLOVE Chemical protection gloves

CATEGORY Cat. III

SIZE RANGE (EU) 8, 9, 10, 11

DIPPING MATERIAL PVC (Vinyl)

THICKNESS 0,7* mm (*chem-layer)

LINING MATERIAL Cotton, Interlock

DEXTERITY 5

GRIP PATTERN Smooth finish

LENGTH RANGE 350 mm

COLOUR Red

PAIRS PER PACKAGE/CARTON 12/60

PIECES PER BOX 0

AQL 0.65 OUTER MATERIAL SPECIFICATION Polyvinyl chloride

INNER MATERIAL SPECIFICATION Cotton

ANTIBACTERIAL/BIOCIDAL TREATMENT Pyrithione zinc (CAS number 13463-41-7)

SIZE	ART. NO.	EAN NO.
10	10PG-10	7392626001084
8	10PG-8	7340118310626
9	10PG-9	7392626062702
11	10PG-11	7340118310619

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 10PG

FEATURES

Protection against chemicals

PREVENTS RISK OF

Corrosive injuries, contact with moisture, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oily and greasy environments, harsh environments

PRIMARY AREAS OF USE

Agricultural work, building and construction, chemical technology work, chemical work, concrete work, construction, decontamination, HVAC installation, marine work, mining, paper industry work, petro-chemical work, sanitation, soil preparation

PRIMARY INDUSTRIES OF USE

Agriculture, mining, oil, gas, petrochemical, pulp and paper, chemical, rubber and plastic, metal fabrication

TYPE OF WORK

Heavy weight

2(4)



CE 0598 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 4121X  EN ISO 374-1:2016/Type B AKL

 EN ISO 374-5:2016
VIRUS



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-15

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 10PG

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN ISO 374-5:2016 Protective gloves against dangerous chemicals and microorganisms – Part 5 Terminology and performance requirements for microorganism risks.

EN ISO 374-1:2016/Type B Protective gloves against

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com



CE 0598 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 4121X  EN ISO 374-1:2016/Type B AKL

 EN ISO 374-5:2016 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-15

TEGERA® 10PG

dangerous chemicals and microorganisms – Part 1:
Terminology and performance requirements for chemical risks.

Test according to EN ISO 374-1:2016

Tested chemical	A	K	L
Permeation level	2	6	3
Degradation %	-19,8	-21,5	-31,9

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480

Definition of breakthrough time through the glove palm (1ugm/cm²/min)

A: Methanol (CAS Number 67-56-1)

K: Sodium hydroxide 40% (CAS number 1310-73-2)

L: Sulphuric acid 96% (CAS number 7664-93-9)



CE 0598 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 4121X  EN ISO 374-1:2016/Type B AKL

 EN ISO 374-5:2016 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-15

4(4)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com