



TEGERA® 7363

Chemical protection glove, fully lined, 0,3* mm (*chem-layer) nitrile, fully dipped, sandy finish, 18 gg, CRF® Technology, glass fibre thread, nylon, polyester, spandex, Cat. III, green, oil and grease resistant, for allround work

PROPERTIES

Extremely good fingertip sensitivity, flexible, durable, excellent grip, excellent grip in oily environments

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. III

SIZE RANGE (EU) 7, 8, 9, 10, 11

DIPPING Fully dipped

DIPPING MATERIAL Nitrile

THICKNESS 0,3* mm (*chem-layer)

LINING Fully lined

LINING MATERIAL 18 gg, CRF® Technology, Glass fibre thread, Nylon, Polyester, Spandex

DEXTERITY 5

GRIP PATTERN Sandy finish

CUFF STYLE Extended safety cuff

LENGTH RANGE 340 mm

COLOUR Green

PAIRS PER PACKAGE/CARTON 12/60

PIECES PER BOX 0

SIZE	ART. NO.	EAN NO.
7	7363-7	7340118326900
8	7363-8	7340118326399
9	7363-9	7340118326511
10	7363-10	7340118326634
11	7363-11	7340118326757

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



CE 0493 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 4X32C  EN 407:2004 X1XXXX

 EN ISO 374-1:2016/Type A AJKMNOPT  EN ISO 374-5:2016 VIRUS



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-09

TEGERA® 7363

FEATURES

Cut resistant according to 388:2016 level C, oil and grease resistant, waterproof

PREVENTS RISK OF

Risk of infection, corrosive injuries, cut injuries, contact with chemicals, contact with moisture, contact with damp, contact with oil, contact with oil and fat

PRIMARY INDUSTRIES OF USE

Mining, pulp and paper, chemical, metal fabrication, automotive, service

TYPE OF WORK

Medium weight

2(4)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 7363

EU-TYPE EXAMINATION

0493 Centexbel, Technologiepark 70, BE-9052 Zwijnaarde (Gent) Belgium

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	3	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	C	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

Suitable for contact with foodstuffs, except for fatty foods

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com



CE 0493 Cat. III

EN 420:2003
+ A1:2009



EN 388:2016
4X32C



EN 407:2004
X1XXXX



EN ISO 374-1:2016/Type A
AJKMNOPT



EN ISO 374-5:2016

VIRUS



NOT FOR
FATTY FOOD



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 7363

EN ISO 374-5:2016 Protective gloves against dangerous chemicals and microorganisms – Part 5 Terminology and performance requirements for microorganism risks.

EN ISO 374-1:2016/Type A Protective gloves against dangerous chemicals and microorganisms – Part 1: Terminology and performance requirements for chemical risks.

Test according to EN ISO 374-1:2016

Tested chemical	A	J	K	M	N	O	P	T
Permeation level	2	5	6	2	3	3	6	6
Degradation %	21,5	5,7	-7,2	5,3	23,8	10,7	-2,0	-7,9

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480

Definition of breakthrough time through the glove palm (l_{ugm}/cm²/min)

A: Methanol (CAS Number 67-56-1)

J: n-Heptane (CAS number 142-82-5)

K: Sodium hydroxide 40% (CAS number 1310-73-2)

M: Nitric acid 65% (CAS number 7697-37-2)

N: Acetic acid 99% (CAS number 64-19-7)

O: Ammonium hydroxide 25% (CAS number 1336-21-6)

P: Hydrogen peroxide 30% (CAS number 7722-84-1)

T: Formaldehyde 37% (CAS number 50-00-0)



CE 0493 Cat. III

EN 420:2003
+ A1:2009



EN 388:2016
4X32C



EN 407:2004
X1XXXX



EN ISO 374-1:2016/Type A
AJKMNOPT



EN ISO 374-5:2016

VIRUS



NOT FOR
FATTY FOOD



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-09

4(4)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com