



CRF®

TEGERA® 913

Cut resistant glove, cut resistance level D, 13 gg, CRF® Technology, glass fibre thread, polyester, Cat. II, blue, approved for handling foodstuffs, extra long, for allround work

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level D

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 16,5

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

LINING MATERIAL 13 gg, CRF® Technology, Glass fibre thread, Polyester

DEXTERITY 5

CUFF STYLE Extended knitwrist cuff

CUFF MATERIAL Textile

COLOUR Blue

PAIRS PER PACKAGE/CARTON 12/60

PIECES PER BOX 0

DISPLAY Bag with euro slot OUTER MATERIAL SPECIFICATION HPPE, glass fibre thread, polyester

SIZE	ART. NO.	EAN NO.
6	913-6	7340118322841
7	913-7	7340118322858
8	913-8	7340118322865
9	913-9	7340118322872
10	913-10	7340118322827
11	913-11	7340118322834

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

**CE** Cat. IIEN 420:2003
+ A1:2009EN 388:2016
3X4XD

TEGERA® 913

FEATURES

Cut resistant according to 388:2016 level D, approved for handling foodstuffs, extra long, soft, thin

PREVENTS RISK OF

Cut injuries, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Cut risk environments

PRIMARY AREAS OF USE

Fishing industry work, food handling, foodstuff handling, hotel- and restaurant work, kitchen work

PRIMARY INDUSTRIES OF USE

Food processing

TYPE OF WORK

Medium weight

2(3)

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 913

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	X	(4)
e) Cut resistance, EN ISO 13997 (N)	D	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

Suitable for contact with foodstuffs



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3X4XD



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com