



AQUATHAN®



Thinsulate
INSULATION

SIZE	ART. NO.	EAN NO.
8	297-8	7392626040106
9	297-9	7392626040113
10	297-10	7392626040120
11	297-11	7392626040137

TEGERA® 297

Leather glove, winter-lined, 0,7-0,8 mm full grain goatskin, neoprene, spandex, Thinsulate™ 100g, Cat. II, black, blue, white, reinforced fingers and thumb, waterproof, hook-and-loop, for allround work

PROPERTIES

High level of protection, good fingertip sensitivity, extra flexible, durable, good grip, perfect fit, extra comfortable, warm

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 8, 9, 10, 11

PALM MATERIAL Full grain goatskin

PALM THICKNESS 0,7-0,8 mm

BACK MATERIAL Neoprene, Spandex

LINING Winter-lined

LINING MATERIAL Thinsulate™ 100g

CLO LINING 1,3 m²·K/W

DEXTERITY 2

CUFF MATERIAL Textile

FASTENING Hook-and-loop

COLOUR Black, Blue, White

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Hook with hangtag OUTER MATERIAL

SPECIFICATION Leather, elastane, polyester, natural latex

MIDDLE MATERIAL SPECIFICATION Polyethylene

INNER MATERIAL SPECIFICATION Polyester

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 297

FEATURES

Reinforced fingers and thumb, pre-curved fingers, waterproof, moisture resistant

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with moisture, contact with damp, contact with cold

PRIMARY ENVIRONMENTS OF USE

Cold environments, wet environments, moist environments

PRIMARY AREAS OF USE

Airport work, building and construction, carpentry, construction, fishing, forest work, hunting, machine driving, machine operating, repair work, sanitation, soil preparation, transport work, warehouse work, wood industry work

PRIMARY INDUSTRIES OF USE

Automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

TYPE OF WORK

Medium weight

2(3)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2111X



EN 511:2006
111



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 297

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 511:2006 Protective gloves against cold



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2111X



EN 511:2006
111



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com