



SIZE	ART. NO.	EAN NO.
11	255-11	7340118301891
10	255-10	7340118301877
12	255-12	7340118301914
9	255-9	7340118301976
8	255-8	7340118301952

TEGERA® 255

Cut resistant glove, fully lined, 0,6-0,7 mm full grain goatskin of top quality, cut resistance level C, KEVLAR® fiber, Cat. II, white, reinforced seams, fibreglass-free, elasticated 180°, for assembly work

PROPERTIES

Perfect fit

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 10,3

SIZE RANGE (EU) 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,6-0,7 mm

LINING Fully lined

LINING MATERIAL KEVLAR® fiber

DEXTERITY 3

FASTENING Elasticated 180°

LENGTH RANGE 225-255 mm

COLOUR White

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Thread OUTER MATERIAL SPECIFICATION Leather, natural latex

INNER MATERIAL SPECIFICATION Para-aramid

TEGERA® 255

FEATURES

Cut resistant according to 388:2003 level 3, cut resistant according to 388:2016 level C, reinforced seams

PREVENTS RISK OF

Prevents risk of: heat injuries, cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Harsh environments

PRIMARY AREAS OF USE

Assembly, engineering, metalwork, sheet-metal work

PRIMARY INDUSTRIES OF USE

Glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, building and construction

TYPE OF WORK

Medium weight

2(3)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2X21C



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-09

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 255

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	C	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2X21C



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-09

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com