



SIZE	ART. NO.	EAN NO.
6	883A-6	7340118322063
7	883A-7	7340118322070
8	883A-8	7340118322087
9	883A-9	7340118322094
10	883A-10	7340118322049
11	883A-11	7340118322056
5	883A-5	7340118381107

TEGERA® 883A

Synthetic glove, nitrile foam, palm-dipped, micro foam grip pattern, 15 gg, Lycra®, nylon, Cat. II, black, grey, water and oil repellent palm, for precision work

PROPERTIES

Highest level of protection, extremely good fingertip sensitivity, extra flexible, very durable, excellent grip, perfect fit, extra comfortable, very breathable, light

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10, 11

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile foam

LINING MATERIAL 15 gg, Lycra®, Nylon

DEXTERITY 5

GRIP PATTERN Micro foam grip pattern

CUFF STYLE Knitwrist cuff

LENGTH RANGE 220-260mm

COLOUR Black, Grey

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Hook with hangtag OUTER MATERIAL SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION Nylon, elastane

ANTIBACTERIAL/BIOCIDAL TREATMENT Pyrithione zinc (CAS number 13463-41-7)

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4131X



EN 407:2004
X1XXXX



TEGERA® 883A

FEATURES

Withstands contact heat up to 100°C, anatomically designed

PREVENTS RISK OF

Abrasion injuries, grazes, scratches, lacerations, contact with damp

PRIMARY ENVIRONMENTS OF USE

Slippery environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Agricultural work, airport work, assembly, building and construction, carpentry, concrete work, construction, electrical installation, engineering, fine assembly, forest work, gardening, HVAC installation, inspection work, installation work, machine driving, machine operating, mining, painting, repair work, sanitation, sheet-metal work, soil preparation, tiling, transport work, warehouse work, wood industry work

PRIMARY INDUSTRIES OF USE

Agriculture, mining, oil, gas, petrochemical, rubber and plastic, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction

TYPE OF WORK

Light weight

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

TEGERA® 883A

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	3	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

CONFIDENCE IN TEXTILES Tested for harmful substances according to Oeko-Tex® Standard 100



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4131X



EN 407:2004
X1XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com