



CRF®

SIZE	ART. NO.	EAN NO.
10	910-10	7392626074514
11	910-11	7392626074538
5	910-5	7340118332734
6	910-6	7392626074552
7	910-7	7392626074576
9	910-9	7392626074613
8	910-8	7392626074668

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

TEGERA® 910

Cut resistant glove, cut resistance level C, 13 gg, CRF® Technology, glass fibre thread, polyester, Cat. II, orange, high visibility colour, for allround work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good fit, comfortable, light

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 12,9

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10, 11

LINING MATERIAL 13 gg, CRF® Technology, Glass fibre thread, Polyester

DEXTERITY 5

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

LENGTH RANGE 220-270 mm

COLOUR Orange

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Bag with euro slot OUTER MATERIAL

SPECIFICATION HPPE, glass fibre thread, polyester, natural latex

TEGERA® 910

FEATURES

Cut resistant according to 388:2016 level C, high visibility colour, soft, thin

PREVENTS RISK OF

Cut injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, clean environments

PRIMARY AREAS OF USE

Assembly, engineering, glass industry work, inspection work, metalwork, repair work, sheet-metal work

PRIMARY INDUSTRIES OF USE

Glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, service

TYPE OF WORK

Medium weight

2(3)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3X4XC



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 910

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	X	(4)
e) Cut resistance, EN ISO 13997 (N)	C	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3X4XC



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com